










FASTENER	SPECIFICATIONS	USAGE	NOTES
 <p>H1040</p>	<p>Self-Drilling Screw 12-14 x 1 1/4" TCP 3 w/o Washer 5/16" Head</p> <p>Color: All Standard SMP & PVDF Check local plant stock inventory Weight: 0.0118 Vintage: C</p>	<p>Wall Structural</p> <p>Used to attach wall panel, wall flashing and light gauge parts with insulation ≤ R13</p>	<p><u>RECOMMENDED TOOL TYPES</u> 2000 RPM MAX Torque adjustable clutch, 4 AMP or higher DO NOT use impacting tools</p> <p><u>DRILLING CAPACITY</u> 0.050 MIN / 0.140 MAX</p> <p>Pre-Drill Diameter: 5/32" Ø</p>
 <p>H1041</p>	<p>Self-Drilling Screw 12-14 x 1 1/4" TCP 3 w/Washer 5/16" Head</p> <p>Color: All Standard SMP & PVDF Check local plant stock inventory Weight: 0.0151 Vintage: C</p>	<p>Wall Structural w/ Washer</p> <p>Used to attach wall panel, wall flashing and light gauge parts with insulation ≤ R13</p>	<p><u>RECOMMENDED TOOL TYPES</u> 2000 RPM MAX Torque adjustable clutch, 4 AMP or higher DO NOT use impacting tools</p> <p><u>DRILLING CAPACITY</u> 0.050 MIN / 0.140 MAX</p> <p>Pre-Drill Diameter: 5/32" Ø</p>
 <p>H1045</p>	<p>Self-Drilling Screw 12-14 x 2" TCP 3 w/o Washer 5/16" Head</p> <p>Color: All Standard SMP & PVDF Check local plant stock inventory Weight: 0.0170 Vintage: C</p>	<p>Wall Structural - Long</p> <p>Used to attach wall panel, wall flashing and light gauge parts with insulation > R13 and ≤ R19</p>	<p><u>RECOMMENDED TOOL TYPES</u> 2000 RPM MAX Torque adjustable clutch, 4 AMP or higher DO NOT use impacting tools</p> <p><u>DRILLING CAPACITY</u> 0.090 MIN / 0.210 MAX</p> <p>Pre-Drill Diameter: 3/16" Ø</p>
 <p>H1047</p>	<p>Self-Drilling Screw 12-14 x 2" TCP 3 w/ Washer 5/16" Head</p> <p>Color: All Standard SMP & PVDF Check local plant stock inventory Weight: 0.0200 Vintage: C</p>	<p>Wall Structural - Long w/ washer</p> <p>Used to attach wall panel, wall flashing and light gauge parts with insulation > R13 and ≤ R19</p>	<p><u>RECOMMENDED TOOL TYPES</u> 2000 RPM MAX Torque adjustable clutch, 4 AMP or higher DO NOT use impacting tools</p> <p><u>DRILLING CAPACITY</u> 0.090 MIN / 0.210 MAX</p> <p>Pre-Drill Diameter: 3/16" Ø</p>
 <p>H1060</p>	<p>Self-Drilling Screw 1/4-14 x 7/8" TCP 1 w/o Washer 5/16" Head</p> <p>Color: All Standard SMP & PVDF Check local plant stock inventory Weight: 0.0101 Vintage: C</p>	<p>Wall Stitch</p> <p>Used to attach wall trim end laps and trim to wall panel</p>	<p><u>RECOMMENDED TOOL TYPES</u> 2000 RPM MAX Torque adjustable clutch, 4 AMP or higher DO NOT use impacting tools</p> <p><u>DRILLING CAPACITY</u> 0.035 MIN / 0.090 MAX</p> <p>Pre-Drill Diameter: 1/8" Ø</p>
 <p>H1061</p>	<p>Self-Drilling Screw 1/4-14 x 7/8" TCP 1 w/ Washer 5/16" Head</p> <p>Color: All Standard SMP & PVDF Check local plant stock inventory Weight: 0.0140 Vintage: C</p>	<p>Wall Stitch w/ Washer</p> <p>Used to attach wall trim end laps and trim to wall panel</p>	<p><u>RECOMMENDED TOOL TYPES</u> 2000 RPM MAX Torque adjustable clutch, 4 AMP or higher DO NOT use impacting tools</p> <p><u>DRILLING CAPACITY</u> 0.035 MIN / 0.090 MAX</p> <p>Pre-Drill Diameter: 1/8" Ø</p>

FASTENER	SPECIFICATIONS	USAGE	NOTES
<p>H1070</p> 	<p>Self-Drilling Screw 12-24 x 1 1/2" TCP 5 w/o Washer 5/16" Head</p> <p>Color: Check w/ local plant</p> <p>Weight: 0.0151 Vintage: C</p>	<p>Wall Structural</p> <p>Used to attach wall panel and trims to hot roll members with insulation ≤ R13</p>	<p><u>RECOMMENDED TOOL TYPES</u> 1800 RPM MAX Torque adjustable clutch, 4 AMP or higher DO NOT use impacting tools</p> <p><u>DRILLING CAPACITY</u> 0.250 MIN / 0.500 MAX</p> <p>Pre-Drill Diameter: 3/16" Ø</p>
<p>H1071</p> 	<p>Self-Drilling Screw 12-24 x 1 1/2" TCP 5 w/ Washer 5/16" Head</p> <p>Color: All Standard SMP & PVDF Check local plant stock inventory</p> <p>Weight: 0.0169 Vintage: A</p>	<p>Wall Structural -HR w/ Washer</p> <p>Used to attach wall panel and trims to hot roll members with insulation ≤ R13</p>	<p><u>RECOMMENDED TOOL TYPES</u> 1800 RPM MAX Torque adjustable clutch, 4 AMP or higher DO NOT use impacting tools</p> <p><u>DRILLING CAPACITY</u> 0.250 MIN / 0.500 MAX</p> <p>Pre-Drill Diameter: 3/16" Ø</p>
<p>H1075</p> 	<p>Self-Drilling Screw 12-24 x 2" TCP 5 w/o Washer 5/16" Head</p> <p>Color: Check w/ local plant</p> <p>Weight: 0.0228 Vintage: D</p>	<p>Wall Structural -HR -Long</p> <p>Used to attach wall panel and trims to hot roll members with insulation > R13 and ≤ R19</p>	<p><u>RECOMMENDED TOOL TYPES</u> 1800 RPM MAX Torque adjustable clutch, 4 AMP or higher DO NOT use impacting tools</p> <p><u>DRILLING CAPACITY</u> 0.250 MIN / 0.500 MAX</p> <p>Pre-Drill Diameter: 3/16" Ø</p>